

### Short communication

---

## Bernoulli equation and the competition of elastic and inertial pressures in the potential flow of a second-order fluid

Daniel D. Joseph

Department of Aerospace Engineering and Mechanics, University of Minnesota, Minneapolis, MN 55455 (USA)

(Received December 16, 1991)

### Abstract

A Bernoulli equation for potential flow of a second order fluid is derived. This equation is used to form an expression for normal extensional stresses at points of stagnation, in which elastic and inertial pressures compete.

*Keywords:* Bernoulli equation; normal extensional stresses; second order fluid

---

The stress  $T$  in an incompressible fluid of second grade is given by

$$T = -p\mathbf{1} + \mu A + \alpha_1 B + \alpha_2 A^2, \quad (1)$$

where  $A = L + L^T$  is the symmetric part of the velocity gradient  $L = \nabla \mathbf{u}$ ,

$$B = A_{,i} + (\mathbf{u} \cdot \nabla)A + AL + L^T A, \quad (2)$$

$\mu$  is the zero shear viscosity,  $\alpha_1 = -n_1/2$  and  $\alpha_2 = n_1 + n_2$  where  $[n_1, n_2] = [N_1(\kappa^2), N_2(\kappa^2)]/\kappa^2$  as  $\kappa \rightarrow 0$  are the constants obtained from the first and second normal stress difference.

The equations of motion are  $\text{div } \mathbf{u} = 0$  and

$$\rho[\mathbf{u}_{,i} + (\mathbf{u} \cdot \nabla)\mathbf{u}] = -\nabla P + \mu \nabla^2 \mathbf{u} + \text{div}[\alpha_1 B + \alpha_2 A^2], \quad (3)$$

---

*Correspondence to:* D.D. Joseph, Department of Aerospace Engineering and Mechanics, University of Minnesota, Minneapolis, MN55455, USA.

where

$$P = p - p_0 - \rho \mathbf{g} \cdot \mathbf{x} \quad (4)$$

is the piezometric pressure,  $p_0$  is a reference pressure and  $\mathbf{g}$  is gravity.

For potential flow

$$\text{curl } \mathbf{u} = 0,$$

$$\mathbf{u} = \nabla \phi,$$

$$\text{div } \mathbf{u} = \nabla^2 \phi = 0,$$

$$(\mathbf{u} \cdot \nabla) \mathbf{u} = \nabla \left( \frac{1}{2} |\mathbf{u}|^2 \right), \quad (5)$$

$$A_{ij} = 2\phi_{,ij},$$

$$A_{ij}^2 = 4\phi_{,il}\phi_{,lj}.$$

Potential flow of a viscous or viscoelastic liquid is incompatible with the no-slip condition at the boundary of the liquid and solid. It is thought that potential flow is a good approximation under certain circumstances outside a thin boundary layer at the forward side of a body (see for example, Rajeswari and Rathna [1], Beard and Walters [2], Davics [3], Leicder and Lilleleht [4]) and dead water region of separated flow at the rear of the body.

Pipkin [5] shows that when (5) holds

$$\text{div } \mathbf{A}^2 = \nabla \gamma^2,$$

$$\text{div } \mathbf{B} = \frac{3}{2} \nabla \gamma^2, \quad (6)$$

where

$$\gamma^2 = \frac{1}{2} \text{tr } \mathbf{A}^2 = 2\phi_{,il}\phi_{,il}. \quad (7)$$

After combining (5)<sub>2</sub>, (5)<sub>3</sub>, (5)<sub>4</sub>, (6)<sub>1</sub>, and (6)<sub>2</sub> with (3), we find that

$$\nabla \left[ \rho \phi_{,i} + \rho |\mathbf{u}|^2/2 + P - \hat{\beta} \gamma^2/2 \right] = 0, \quad (8)$$

where  $\hat{\beta} = 3\alpha_1 + 2\alpha_2$  is the climbing constant and it is typically positive,  $\hat{\beta} > 0$  [6]. Hence,

$$\rho \phi_{,i} + \rho |\mathbf{u}|^2/2 + P - \hat{\beta} \gamma^2/2 = C. \quad (9)$$

Equation (9) defines the Bernoulli equation for potential flow of a second order fluid. This equation may be simplified for steady flow with uniform streaming  $U$  at infinity and  $\gamma = p - \rho \mathbf{g} \cdot \mathbf{x} = 0$  far from the body. In this case

$$\rho |\mathbf{u}|^2/2 + P - \hat{\beta} \phi_{,il}\phi_{,il} = \rho U^2/2. \quad (10)$$

Returning next to (1) with (4) and (9), we may eliminate  $p$ . Then

$$\sigma_{ij} = - \left[ C + \hat{\beta} \phi_{,il} \phi_{,il} - \rho \phi_{,t} - \rho |\mathbf{u}|^2/2 \right] \delta_{ij} + 2 \left[ \mu + \alpha_1 (\partial_t + \mathbf{u} \cdot \nabla) \right] \phi_{ij} + 4(\alpha_1 + \alpha_2) \phi_{,il} \phi_{,lj}, \quad (11)$$

where

$$\sigma_{ij} = T_{ij} + \rho \mathbf{g} \cdot \mathbf{x} \delta_{ij} \quad (12)$$

is the active dynamic stress. In the diagonal coordinates  $x_1, x_2, x_3$  of the frame in which  $\phi_{,ij}$  is diagonal

$$[\phi_{,ij}] = \begin{bmatrix} \lambda_1 & 0 & 0 \\ 0 & \lambda_2 & 0 \\ 0 & 0 & \lambda_3 \end{bmatrix}, \quad (13)$$

we have

$$\begin{aligned} \begin{bmatrix} \sigma_{11} & 0 & 0 \\ 0 & \sigma_{22} & 0 \\ 0 & 0 & \sigma_{33} \end{bmatrix} &= - \left[ C - \rho \phi_{,t} - \rho |\mathbf{u}|^2/2 \right. \\ &\quad \left. + \hat{\beta} (\lambda_1^2 + \lambda_2^2 + \lambda_3^2) \right] \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} \\ &\quad + 2 \left[ \mu + \alpha_1 (\partial_t + \nabla \phi \cdot \nabla) \right] \begin{bmatrix} \lambda_1 & 0 & 0 \\ 0 & \lambda_2 & 0 \\ 0 & 0 & \lambda_3 \end{bmatrix} \\ &\quad + 4(\alpha_1 + \alpha_2) \begin{bmatrix} \lambda_1^2 & 0 & 0 \\ 0 & \lambda_2^2 & 0 \\ 0 & 0 & \lambda_3^2 \end{bmatrix}, \quad (14) \end{aligned}$$

where

$$\alpha_1 + \alpha_2 = \frac{1}{2} n_1 + n_2 > 0 \quad (15)$$

in all viscoelastic fluids known to me.

The case of flow at the stagnation points of a body in steady flow, in an arbitrary direction is of special interest. The steady streaming past a stationary body is equivalent, under a Galilean transformation, to the steady motion of a body in an otherwise quiet fluid. The potential flow of a fluid near a point  $(x_1, x_2, x_3) = (0, 0, 0)$  of stagnation is a purely extensional motion with

$$[\lambda_2, \lambda_2, \lambda_3] = \frac{U}{L} \dot{S} [2, -1, -1], \quad (16)$$

where  $\dot{S}$  is the dimensionless rate of stretching in the direction  $x_1$ ,  $L$  is the scale of length and

$$[u_1, u_2, u_3] = \frac{U}{L} \dot{S} [2x_1, -x_2, -x_3]. \quad (17)$$

In this case

$$\begin{aligned} \begin{bmatrix} \sigma_{11} & 0 & 0 \\ 0 & \sigma_{22} & 0 \\ 0 & 0 & \sigma_{33} \end{bmatrix} &= \frac{\rho}{2} \left[ \frac{U^2}{L^2} \dot{S}^2 (4x_1^2 + x_2^2 + x_3^2) - U^2 \right] \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} \\ &+ \mu \frac{U}{L} \dot{S} \begin{bmatrix} 2 & 0 & 0 \\ 0 & -1 & 0 \\ 0 & 0 & -1 \end{bmatrix} \\ &+ 2 \frac{U^2}{L^2} \dot{S}^2 \begin{bmatrix} -\alpha_1 + 2\alpha_2 & 0 & 0 \\ 0 & -7\alpha_1 - 4\alpha_2 & 0 \\ 0 & 0 & -7\alpha_1 - 4\alpha_2 \end{bmatrix}. \end{aligned} \quad (18)$$

At the stagnation point itself

$$\sigma_{11} = -\frac{\rho}{2} U^2 + 2\mu \dot{S} + 2(2\alpha_2 - \alpha_1) \frac{U^2}{L^2} \dot{S}^2. \quad (19)$$

Since  $\alpha_1 < 0$ ,  $2\alpha_2 - \alpha_1 = \frac{5}{2}n_1 + 2n_2 > 0$ , the normal stress term in (19) is positive, independent of the sign of  $\dot{S}$ , but  $2\mu\dot{S}$  is negative at the front side of a falling body and is positive at the rear. This is a new manifestation of the competition between inertia and normal stress, which I believe plays a major role in recently observed flow induced anisotropy [7]. This causes long bodies to float broadside on when the ratio of inertial pressure to normal (extensional) stress is large, and long-side on in the other case. The same flow induced anisotropy causes suspensions of solid spheres to develop cross stream structure when the ratio is high, and to hook together in vertical chains when it is low.

Dimensionless groups may be formed from the ratios of inertia  $\rho U^2/2$ , viscosity  $2\mu U/L$  and normal-extensional stresses  $(5n_1 + 4n_2)U^2/L^2$ . We could again speak of an inertial radius (Joseph [6]) for the competition between inertial and normal-extensional stress with inertia dominant when  $L > L_c$  and normal stress dominant when  $L < L_c$  where

$$L_c^2 \approx \frac{10n_1 + 8n_2}{\rho}.$$

is a material property. Riddle et al. [8] discovered that if the initial separation of two spheres settling along their line of centers in a viscoelastic fluid is larger than a certain critical separation the spheres will diverge, whereas if it is smaller than this separation they will converge. This is consistent with the notion that the critical separation is the inertial radius  $L_c$ .

Every potential flow is a solution of the equations of motion for a fluid of second grade with stresses given by (11). Such solutions do not generally satisfy the condition of no-slip at solid boundaries.

### Acknowledgments

This work was supported by the NSF, fluid, particulate and hydraulic systems; by the US Army, Mathematics and the DOE, Department of Basic Energy Sciences.

### References

- 1 G.K. Rajeswari and S.L. Rathna, Flow of a particular class of visco-elastic and visco-in-elastic fluids near a stagnation point, *Z. Angew. Math. Phys.*, 13 (1962) 43–57.
- 2 D.W. Beard and K. Walters, Elastico-viscous boundary-layer flow J. two-dimensional flow near a stagnation point. *Proc. Comb. Phil Soc.*, 60 (1964) 667–674.
- 3 M.H. Davics, A note on elastico-viscous boundary layer flows, *Z. Angew. Math. Phys.*, 17 (1966) 189–190.
- 4 P.J. Leider and S.V. Lilleleht, Viscoelastic behavior in stagnation flow. *Trans. Soc Rheol.*, 17 (1973) 501–524.
- 5 A.C. Pipkin, Nonlinear phenomena in continua in nonlinear continuum theories in mechanics and physics and their applications “Edizione Cremonese,” Roma, pp. 51–150, (1970). See also: A.C. Pipkin and R. Tanner, in: S. Nemat-Nasser (Ed.), *A survey of theory and experiment in viscometric flows of viscoelastic liquid in mechanics today*, Vol. 1, Pergamon, 1972.
- 6 D.D. Joseph, *Fluid Dynamics of Viscoelastic Liquid*, Springer Verlag, 1990.
- 7 D.D. Joseph, J. Nelson and H. Hu, Flow induced anisotropy in suspensions of solid particles in viscous and viscoelastic liquids. AHPARC preprint 91-126 (to appear).
- 8 M.J. Riddle, C. Navarez and R. Bird, Interactions between two spheres falling along their line of centers in a viscoelastic fluid. *J. Non-Newtonian Fluid Mech.*, 2 (1977) 23–35.